

CF-691 全自動貼袋機


Fully Automatic Patch Pocket Machine



特點 FEATURES


1. 優美的外觀，世面最具性價比的全自動貼袋機；
2. 人性化的換模體驗，低成本的模具更換（本機能適應市面上大部分大小和袋型的口袋）；
3. XY軸均采用絲杆導軌加鬆下伺服電機控制（這樣的配置在模板機市場上屬於是頂配）；
4. 在不更換原裝機頭電機的前提下，全機採用單一觸摸屏控制，保留了原裝機頭的性能，又讓整機操作更加一體化，簡單化。
5. 原廠標配日本Brother S-7300和JUKI DDL-9000C，均是日本最新款縫紉機頭。

1. The fully automatic patch pocket machine features beautiful appearance and highest cost performance
2. With people-oriented mould replacing experience, low-cost mould replacing (the machine is capable of adapting most pockets of different sizes and shapes in the market)
3. The X and Y shafts adopt screw rod guiderail with Panasonic servo motor control (such configuration is top in the market of the template machine)
4. Under the precondition without replacing the original machine head, the whole machine adopts single touch screen control with the performance of the original machine head, and features integrated and simple operation
5. It is equipped with original Japanese Brother S-7300 and JUKI DDL-9000C, which are the latest sewing machine head made in Japan



可以适应市面上大部分不同大小与形状的袋子，只需更换折刀，成本非常低，且调整方便。

It is capable of adapting most pockets of different sizes and shapes in the market, and only requires replacing the pocket knife, and features very low cost and convenient adjustment.



气缸固定模具，避免人工固定螺栓造成的误差，安装也变得十分的方便。

The mould is fixed with cylinder for avoiding error caused by manual operation, therefore, installation is also very convenient.



全机使用单一触摸屏操作，操作将不再繁琐。

The whole machine is operated with single touch screen, and boasts simple operation



该机标配使用Brother S-7300和JUKI DDL-9000C，均是日本最新一代缝紉机头。

This machine adopts Brother S-7300 and JUKI DDL-9000C, which are the latest sewing machine head made in Japan

頭部裝置	最高轉速	縫制針距	送布方式	縫制範圍	綫迹形式	工作電壓	工作氣壓	設備尺寸	包裝尺寸	工作效率	
Head Device	Highest Rotational Speed	Sewing Needle Pitch	Cloth Feeding Mode	Sewing Range	Stitch Type	Working Voltage	Working Air Pressure	Equipment Dimension	Package Dimension	Working Efficiency	
Brother S-7300/JUKI DDL-9000C	3000rpm	1-3mm	X/Y方向伺服送布	X=200mm Y=210mm	單或雙綫迹	220V	0.5Mpa	1620 × 1570 × 1360mm	1220 × 1120 × 1010mm	單人單機 4件/分鐘	單人雙機 8件/分鐘